## TP805 3" Thermal Receipt Printer

- High printing speed up to 250mm/s
- Three-in-one interface, including RS232, Ethernet and USB
- Embedded with 2D barcode edition algorithm which supports the 2D barcode common in the market, such as QRcode/PDF417
- Provide Windows/Linux driver
- Provide complete OPOS driver
- Support page mode printing
- With double cash drawer driver
- Movable paper guard plate design which supports 58mm, 76mm, 80mm wide thermal paper







Metallic Printer Enclosure

Wide-range of Interfaces

Wall Mounted Kit

## Specification

Item		Parameter
Printing	Print Method	Direct Thermal Line Printing
	Resolution	Standard 203dpi (8dots/mm), Emulated 180dpi(7dots/mm)
	Print Speed	Max. 250mm/s
	Printing Width	48mm/72mm
Interface	Standard	USB+Serial+Ethernet,
	Optional	Parallel, Bluetooth or Wi-Fi
Page Mode		Support
Memory	RAM	16Mb
	Flash	32Mb
Fonts	Chinese	GBK 24×24dots
	Alphanumeric	ASCII 9×17, 12×24dots
	User-defined	YES
	Codepage	48
Barcode	1D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR,
		CODE128, CODE93
	2D	PDF417, QR code
		Support bitmap printing with different density and user
Graphics		defined bitmap printing. (Max size of each bitmap is 40K,
		the total size of bitmap is 256k)
Detection	Sensors	Paper out detection, cover open detection,
LED Indicator	Power	Green LED
	Paper	Red LED
	Error	Red LED
Reliability	TPH life	150km
	Cutter life	1.5 million cuts



	Input	AC 100V-240V 50-60HZ
Power Supply	Output	DC 24V/2A
	Paper Type	Thermal Receipt Paper
	Paper Width	58mm/80mm
D	Paper Thickness	0.056~0.1mm
Paper	Roll Paper Diameter	Max. OD cp83mm
	Paper Load	Easy paper loading
	Paper Cut	Partial cut or full cut
	Operation	0°C~40°C, 20%~85%RH
Environment	Storage	-20°C~70°C, 5%~95%RH
Physical	Dimension	195(L)x147(W)x147(H)mm
Characteristics	Weight	1.8KG
		USB/Serial/Parallel Cable, Paper
Options & Aco	cessories	Roll, Power Adapter, Power Cord,
		CD, Quick Start Guide
	Emulation	ESC/POS
	Driver	XP / Win7/Win8 /Win10/POSReady
Software		/Linux /OPOS
	SDK	WinCE, Win Mobile, Android















